

## Analysing with ONE view

```
$ maqao oneview --create-report=one -options=...
```

### **Main options:**

- `--binary=bin_path`: Path to application executable. Can be relative.
- `--run-command=run_cmd`: Command to run the application, using keyword `<binary>` to reference `bin_path`. If omitted, considered to be `./<binary>`
- `-xp=exp_dir`: Path to directory storing the results. If omitted, directory `maqao_<timestamp>` will be created in the current directory.
- `--output-format=out_format`: Output format. Accepted values are `html` (default), `xlsx`, `text` and `all` (for all three formats).

### **Parallel options:**

- `--omp-num-threads=num`: Number of OpenMP threads. Will initialise the `OMP_NUM_THREADS` environment variable.
- `--mpi-command=mpi_cmd`: MPI runtime invocation. Will prepend `run_cmd`.

### **Batch scheduling options:**

- `--batch-script=script_path`: Path to job scheduler script. The script must have been modified to replace the application executable and its arguments with keyword `<run_command>`.
- `--batch-command=batch_cmd`: Command for invoking the job scheduler, using keyword `<batch_script>` to reference `script_path`.

### **Using a configuration file for ONE View:**

- `--config=config_path`: Uses file `config_path` to retrieve options. Options in `config_path` are identical to those from command line (without the `--`) and declared as Lua variables (`option="value"` or `option=number`).
- `--create-config=sample_config`: Generates a sample configuration file. If `sample_config` is omitted, file `"config.lua"` will be created in the current directory.

### **Viewing results:**

- Text results are displayed directly on the console output.
- HTML and XLSX results are generated in directory `<exp_dir>/RESULTS/`
  - HTML results are in subdirectory `<binary_name>_one_html`. Open file `index.html` in this directory to display them in your browser.
  - XLSX results are in file `<binary_name>_one_0_0.xlsx`
- The path to the HTML/XLSX results are displayed at the end of ONE View analysis.

## Sample invocations of ONE View

- Command line on interactive MPI run

```
$ maqao oneview --create-report=one --binary=my_path/my_app \
--mpi-command="mpirun -n 4" --omp-num-threads=2
```

- Command line for job scheduler script (script must be edited to replace `my_path/my_app -arg=foo` with `<run_command>`)

```
$ maqao oneview --create-report=one --binary=my_path/my_app \
--run-command="<binary> -arg=foo" \
--batch-script="my_script.job" \
--batch-command="my_jobsched <batch_script>"
```

- Using ONE View configuration file

```
$ maqao oneview --create-config=my_config.lua
{edit my_config.lua to fill useful variables}
$ maqao oneview --create-report=one --config=my_config.lua
```

## Advanced: Invoking LProf / CQA separately

### Profiling with MAQAO LProf

- Sequential / OpenMP profiling

If *exp\_dir* is omitted, a directory named *maqao\_lprof\_<timestamp>* will be created.

```
$ maqao lprof [-xp=exp_dir] -- ./foo arg1 arg2 ...
```

- MPI / hybrid profiling

```
$ maqao lprof [-xp=exp_dir] --mpi-command="mpirun -n 32" \
-- ./foo arg
```

- Displaying profiling results

```
$ maqao lprof -xp=exp_dir -df # Functions profiling results
$ maqao lprof -xp=exp_dir -dl # Loops profiling results
```

### Analysis with CQA

- Analysing a given loop or set of loops

*id1, id2, id3 ...* are the numerical loop identifiers returned by **LProf**.

```
$ maqao cqa ./my_app -loop=id1,id2,id3...
```

- Analysing all innermost loops in a given function or set of functions

```
$ maqao cqa ./my_app -fct-loops="regexp"
```

- Analysing the body of a given function or set of functions

*regexp* is a regular expression: *foo* matches "foo1", "foo" or "afoo", while *^bar\$* matches "bar" only

```
$ maqao cqa ./my_app fct-body="regexp"
```